

Tyrecheckers

TYRE PRESSURE INDICATORS

Motorcycle Wireless Tyre Pressure & Temperature Monitoring System (2 wheels)

Model No: TD-4000A-X (Tyre Pressure & Temp. Monitoring System)

Price: AUD \$299



Receiver Unit

Operating environment

- Operating temperature range -30 deg to 85 deg C
- Storage temperature range -40 deg to 105 deg C
- Operating humidity 100%
- Vibration 3.5mm 10 Hz in X,Y and Z direction

Power

- Operating Voltage: 1.5V DC
- Battery Life: Approx. 6 to 12 Months (4hr/day)
- Battery type AAA 1.5V (x1)

Dimensions TD-4000A

- Weight 43 g
- Size L 58mm * W 36mm* D 19mm
- LCD View size L 28.5mm * W 17.5mm

System

- System frequency at 433 MHz
- Sensor pressure range 0-60 psi
- Sensor pressure sensitivity ± 0.5 psi
- Sensor temperature sensitivity ± 2 deg C
- Low power consumption in sensor
- Transmission length 10m to 20 m
- Receiver sensitivity is -112dBm

What's Included in the Kit?

- 1 x Receiver unit / monitor
- 2 x Wireless Sensors
- 1 x AAA Batteries
- 2 x CR1632 3V Batteries
- 2 x Anti-theft nuts

Threshold Settings

- Selectable Low Tyre Pressure Warning Range: 10 to 50 PSI
- Selectable High Tyre Pressure Warning Range: 21 to 60 PSI
- Selectable High Temperature Warning Range: 40 to 100 Degrees Celsius



Sensor Unit

Operating environment

- Operating temperature range -30 deg to 145 deg C
- Storage temperature range -40 deg to 145 deg C
- Operating humidity 100%
- Shock >500G from 1m height
- Vibration 3.5mm 10 Hz in X,Y and Z direction

Power

- Sensor is equipped with battery - CR1632 (3V)
- Battery Life - Approx. 1 Year

Dimensions TD-4000A Sensor

- Weight - 10g \pm 1 g
- Size - Diameter 18.5mm / Height 20mm

* All products come with a 12 month warranty.